



# K Series Stations — Polypropylene Enclosure

## One-Speed and Two-Speed Control

Catalog Number	Description	Enclosure Size
<b>Complete Pendant Stations</b>		
Each station includes switches listed plus a standard package of legend plates (see page 6), Neoprene multi-step cord grip, strain relief bracket and Neoprene boots.		
<b>K2-1</b>	Two One-Speed Switches	Two-Button
<b>K2-2A</b>	Two Two-Speed Switches	Two-Button
<b>K2-1M</b>	Two One-Speed Switches with K-6A1 Maintained On/Off Switch	Two-Button
<b>K2-2AM</b>	Two Two-Speed Switches with K-6A1 Maintained On/Off Switch	Two-Button
<b>K4-1</b>	Four One-Speed Switches	Four-Button
<b>K4-2A</b>	Four Two-Speed Switches	Four-Button
<b>K4-1M</b>	Four One-Speed Switches with K-6A1 Maintained On/Off Switch	Four-Button
<b>K4-2AM</b>	Four Two-Speed Switches with K-6A1 Maintained On/Off Switch	Four-Button
<b>K6-1</b>	Six One-Speed Switches	Six-Button
<b>K6-2A</b>	Six Two-Speed Switches	Six-Button
<b>K6-1M</b>	Six One-Speed Switches with K-6A1 Maintained On/Off Switch	Six-Button
<b>K6-2AM</b>	Six Two-Speed Switches with K-6A1 Maintained On/Off Switch	Six-Button



### Enclosures

Each complete enclosure includes a standard package of legend plates (see page 6), Neoprene multi-step cord grip, strain relief bracket and Neoprene boots.

<b>K-2</b>	Two-Button plus Accessory Space
<b>K-4</b>	Four-Button plus Accessory Space
<b>K-6</b>	Six-Button plus Accessory Space

### Switches

<b>RB-1</b>	One-Speed Switch (with one set normally open and one set normally closed contacts)
<b>RB-2A</b>	Two-Speed Switch (one set normally closed and two normally open cumulative type "Make-Make" contacts)
<b>K-1A</b>	SPST, N/O Contact Momentary Switch
<b>RPS-6</b>	On/Off Toggle Switch with Neoprene Boot
<b>K-6A1</b>	Maintained Push-On/Push-Off Switch (includes push On/Off legend plate and Red Neoprene Boot)
<b>PB-STA</b>	Momentary On/Off Switch, Two Buttons, One Hole (NEMA 1 and 2)
<b>PB-STMA</b>	Maintained On/Off Switch, Two Buttons, One Hole (NEMA 1 and 2)

### Catalog Number

### Accessories

<b>RPS-7</b>	Key Switch (NEMA 1 and 2)
<b>RPS-PL</b>	Pilot Light, 115 VAC (NEMA 1 and 2)
<b>KW-2</b>	Black Neoprene Boot
<b>KW-2R</b>	Red Neoprene Boot
<b>K-CG-B-2</b>	Black Neoprene Multi-Step Cord Grip Boot, for .420 to .695 Diameter Cable
<b>K-CG-B-3</b>	Full Top Shroud Boot for .420 to .695 Diameter Cable. Recommended for outdoor or wet environments.
<b>PT-7</b>	Key Switch
<b>PT-11</b>	Two-Way Selector Switch (A-B)
<b>PT-12</b>	Three-Way Selector Switch (A-Both-B)
<b>PT-16</b>	Three Way Positive Selector Switch (A-Off-B)
<b>PT-STMM</b>	Mushroom Emergency On/Off Switch

RB-1 and RB-2A Switch Ratings	
Voltage	AC Amps
28	10
125	10
*Switches Not Suitable for DC Circuits	

Dimensions and Weights					
Enclosure Size	Dimensions — Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
Two-Button	3-1/2	2-1/4	8-1/4	7/8	.420-.695
Four-Button	3-1/2	2-1/4	12	1-1/8	.420-.695
Six-Button	3-1/2	2-1/4	15	1-1/2	.420-.695